

EASY PANELS

Wall Panels Installation Guide

Please read the following information carefully before you begin installing your wall panels.



Tools & Materials

Here is a checklist of what you require to install your panels:

- Adhesive
- Silicone
- Trims
- Spirit Level
- Tape Measure
- Handsaw
- Hacksaw
- Pencil



Preparation

- PVC is commonly known to expand slightly in humid conditions. So prior to carrying out any work, allow 24 hours for your panels to climatise with the environment.

- Clean the work area before installing panels making sure to remove film, dirt and other residue.



Tips and Advice

- Some of your panels come with protective film, if you leave this on while cutting it will help prevent scratches.

- There are lots of ways to cut panels. So we'd recommend practising on unwanted sections first & double check measurements.

- Health and safety should be observed throughout your project and always wear protective glasses when cutting to avoid irritation.



Step A - Corners

- 1 Start off by cutting the internal corner trim to height using a hacksaw.
- 2 Apply the adhesive to the edges of the internal corner and fix to the wall (You can use masking tape to temporarily secure).
- 3 Slot a panel directly into the trim on the left side, mark the position onto the wall and then repeat for the right (use the spirit level to ensure even).

Step B - Fixing

- 4 For each wall of the project are deduct 15mm for the bottom, top & middle to allow for the corners.
- 5 Cut using a hacksaw with the decorative side facing up.
- 6 Double check panels are cut correctly and then apply adhesive to the back of your panel and silicone on the inside corner. Place panels against wall and smooth out air pockets. To ensure watertight run a bead of silicone into the groove before repeating the process for each panel.
- 7 Apply silicone to the inside end caps to ensure watertight and apply adhesive on the outer edge for fixing to wall.
- 8 If pipes and other fittings need to be incorporated fill in the outside of the 2- 3mm expansion gap with silicone.

Wall Panels Installation Guide

Check out our website or youtube channel for handy video tutorials.



Maintenance

Everyday cleaning agents are recommended ie hot soapy water and a non abrahasive cloth. Solvents are not advisable. It may also be helpful to wipe down exceive water with a soft, dry cloth to avoid discolourisation. Wall panels are suitable for use in tempratures of -20 to +60 degrees celsius.

Performance

PVC wall panels are for internal use only, when installed and maintaned as per our instructions the product is covered by a 10 year guarntee. Only use a low adhesive masking tape and remove immediately afterwards. Class 1 fire Certification for most products. Please check.

Disclaimer

During manufacture a some variation in pattern or shade can occur. An ample quantity of panels for the area to be covered should be obtained in one shipment all of the same manufacture date to ensure consistence. No liability can be accepted after panels have been fitted.

